

SECTION 731 RAISED PAVEMENT MARKERS

MATERIAL		REFERENCE	PURP.	SAMPLED BY	MIN. FREQ.	MIN. QUANT.	CERT.	SMALL QUANTITY	TYPICAL HANDLING TIME	REMARKS
		TESTED BY		METHOD		CONTAINER	DISTR.			
ADHESIVE (For Pavement Markers)	Bituminous	731.02(b)(1) 1015.09 Mat. Lab	Prelim. Source Approval	Dist. Lab S 606	1/lot	0.5 gal Friction top can	-----	-----	21 days	(QPL 59)
		731.02(b)(1) 1015.09 Mat. Lab	Accept.	Proj. Engr. S 606	*	0.5 gal Friction top can	CD 1 & 7	-----	11 days	(QPL 59) *When not accompanied by CD. See S 606 for details.
	Epoxy	731.02(b)(2) 1017.02 Mat. Lab	Prelim. Source Approval	Dist. Lab S 606	1/lot/ component	0.5 gal Friction top can	-----	-----	21 days	(QPL 32)
		731.02(b)(2) 1017.02 Mat. Lab	Accept.	Proj. Engr. S 606	*	0.5 gal Friction top can	CD 1 & 7	-----	11 days	(QPL 32) *When not accompanied by CD. See S 606 for details.
RAISED PAVEMENT MARKERS		731.02(a) 1015.09 Mat. Lab	Prelim. Source Approval	Dist. Lab S 607	1/10,000/ type/source	20 markers	-----	-----	14 days	(QPL 9)
		731.02(a) 1015.09 Mat. Lab	Accept.	Proj. Engr. S 607	*	20 markers	CD 1 & 7	-----	10 days	(QPL 9) *When not accompanied by CD. See S 607 for details.