



T.B.M. \*106  
60d NAIL ROOT OF 4.0 LIVE OAK  
20.85' LT. OF STA. 178+22.53  
ELEV. 17.82

T.B.M. \*107  
60d NAIL IN POWER POLE  
33.73' RT. OF STA. 185+95.77  
ELEV. 20.73'

**CURVE DATA**

P.I. STATION	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19
$\Delta$	0-49°06.00" LT.	1-43°14.00" RT.	2-08°19.00" LT.	1-39°50.00" RT.	91-02°03.00" RT.	11-53°06.00" LT.	40-01°59.00" LT.	10-04°26.00" LT.	20-25°46.00" LT.	1-32°41.00" LT.	14-12°43.00" RT.	8-49°24.00" RT.	8-43°21.00" RT.	8-26°56.00" RT.	2-34°59.00" LT.	6-13°19.00" RT.	51-41°11.00" LT.	6-41°11.00" RT.	44-38°30.52" RT.
D	0-26°59.40"	0-57°35.58"	0-38°57.19"	1-19°27.36"	70-10°20.71"	17-47°39.38"	60-15°38.16"	11-45°32.44"	8-57°24.49"	1-37°37.25"	5-40°27.11"	5-15°36.23"	6-24°22.84"	6-16°58.74"	1-23°07.14"	2-07°57.34"	28-28°54.08"	4-55°38.17"	88-58°06.97"
T	90.96'	89.63'	164.73'	62.83'	83.14'	33.52'	34.64'	42.95'	115.27'	47.47'	128.88'	84.04'	68.21'	67.36'	93.25'	146.02'	104.79'	67.93'	26.44'
L	181.92'	179.25'	329.41'	125.65'	129.73'	66.43'	85.67'	125.09'	228.09'	167.74'	136.15'	134.47'	186.46'	291.75'	195.18'	135.70'	50.18'		
R	12737.08'	5969.04'	8825.32'	4326.60'	81.65'	321.99'	95.08'	487.25'	639.69'	3521.53'	1009.76'	1089.26'	894.36'	911.92'	4135.93'	2686.67'	216.36'	1162.83'	64.40'

Figure 8-27b: TBMs and Reference Points