

STATE OF LOUISIANA
DEPARTMENT OF TRANSPORTATION AND DEVELOPMENT
MATERIALS & TESTING SECTION
5080 FLORIDA BLVD., BATON ROUGE, LA 70806

**CERTIFICATE OF DELIVERY
FOR
ASPHALTIC MATERIALS**

PROJECT NAME _____ P. O. NUMBER _____
PROJECT NUMBER _____ CONTRACTOR _____

TYPE ASPHALT	PRODUCT SOURCE CODE	QUANTITY (GALLONS)	REFINERY	REFINERY LOCATION
DESTINATION				REFINERY TANK NUMBER

CHECK ONE: Distributed to: ☐ Distributor ☐ Truck (License No. _____)

NOTE TO SUPPLIER: The supplier is required to enter the following results for the above referenced DOTD Lab No.

ROTATIONAL VISCOSITY @135°C, Pa
RECOMMENDED MIXING TEMPERATURE MINIMUM _____ °F, MAXIMUM _____ °F
(Mixing Temperature shall not exceed 350°)
RECOMMENDED COMPACTION TEMPERATURE MINIMUM _____ °F, MAXIMUM _____ °F

NOTE TO CONTRACTOR: Binders with rotational viscosity values higher than 3.0 Pa should be used with caution only after consulting with the supplier as to any special handling procedures and guarantees of mixability and pumpability.

The undersigned certifies that the asphalt in this shipment is the same asphalt as indicated above and that preliminary source testing has been conducted by the Materials and Testing Laboratory and that this material meets all specification requirements for the intended use of the designated project.

**This certificate is invalid unless signed by an
authorized representative of the company.**

COMPANY: _____

BY: _____
(Authorized Company Representative Signature)

Copies: Two copies shall accompany all shipments:

- One copy for the Project or Maintenance Engineer and one copy to the District Laboratory Engineer.
- One copy shall be mailed to the Materials Engineer Administrator, LA DOTD, 5080 Florida Blvd., Baton Rouge, LA 70806.

For DOTD Use:

Approved: _____ Date: _____

Remarks: _____

Shipments will be accepted only when accompanied by this official DOTD certificate form.